

3/10/05

10/531 273
JC13 PCT/PTO 13 APR 2005

1

REPLACED BY
PCT/PTO

FUEL FILTER FOR DIESEL ENGINES WITH HIGH PRESSURE DIRECT INJECTION OF COMMON RAIL TYPE AND THE LIKE

This invention relates to a filter for vehicle fuel, in particular for diesel
5 engines of common rail or high pressure direct injection type, and the like.
In these types of engine the fuel feed rate to the engine feed pump is
much greater than that required by the engine for its operation, as the fuel
is used not only as engine feed fluid but also as the lubrication fluid and
cooling fluid for the feed pump. That fuel not fed to the cylinders
10 increases in temperature as it removes heat from the pump and is then
returned to the vehicle fuel tank.

It has been found that because of the high temperature at which the feed
pump operates, after a certain time of engine operation the fuel contained
in the vehicle tank or in the engine feed circuit attains a high temperature,
15 of the order of 100°C and beyond.

A requirement has therefore arisen to control the fuel temperature as too
high a fuel temperature could damage components of the engine feed
circuit. Moreover in these types of engine the fuel temperature has
become an essential parameter in regulating the fuel feed rate to the
20 engine. Measuring the fuel temperature has hence become necessary for
correct engine operation. The value of the measured temperature is fed
to the electronic control unit which controls fuel feed to the pump and
hence to the cylinders.

The known art has solved this need to control the fuel temperature by
25 temperature measurement devices positioned either inside the fuel tank or
along the conduits through which the fuel is fed to the engine.

In both cases the devices used require suitable fixing flanges and electric cables for connecting the device to the vehicle electronic control unit. Moreover it is often difficult to install said temperature measurement devices as that engine region in which the conduits are present is crowded
5 with numerous components.

The object of the present invention is to overcome the drawbacks of the known art within the context of a simple and rational solution of low cost. The invention attains said object by virtue of the characteristics defined in the claims.

10 Specifically, the invention provides a temperature measurement device which is associated with the lower part of the fuel filter installed on the vehicle.

According to a preferred embodiment of the invention, said temperature measurement device is associated with the means for sensing the
15 presence of water accumulated in the bottom of the fuel filter.

In this respect it is known that the water present in the fuel tends to create oxidation damage to the metal parts with which it comes into contact, hence the latest generation of filters, in particular for diesel engine fuel, separate not only the impurities but also the water present in the fuel.

20 As water has a specific gravity greater than the fuel, it collects on the bottom of a collection chamber positioned in the lower part of the filter. This water must be bled off on reaching a maximum level, to avoid it interfering with correct filter operation, or it may be returned to the fuel flow leaving the filter.

The water is bled off by suitable means which are activated when a suitable sensor senses that the water in said collection chamber has reached its maximum level.

Said means for sensing the water level comprise a float positioned within
5 the collection chamber and having a specific gravity between the specific gravity of water and the specific gravity of the fuel. The float is mounted on a guide stem, in the interior of which a magnetic field sensor is positioned connected electrically to an electronic card by two conductors. According to the invention, said stem also internally houses the
10 temperature sensor which measures the fuel temperature. Specifically, said temperature sensor is housed in proximity to the free end of the stem, which projects into the water collection chamber. To facilitate heat conduction the sensor is embedded in a conductive resin which is poured into the stem.

15 The invention is described in detail hereinafter with the aid of the accompanying figures, which illustrate a non-exclusive embodiment thereof by way of example.

Figure 1 is a schematic illustration of the filter according to the invention;

Figure 2 is an enlarged view of the lower portion of Figure 1;

20 Figure 3 is an enlarged view of the lower portion of the filter, on which a variant of the invention is installed.

Figure 1 shows a filter 1, substantially of known type, comprising an outer casing 2 having a fuel inlet 3 and outlet 4. Said casing 2 houses internally a filter means 5 positioned within an upper chamber 6. The fuel enters
25 the chamber 6 through the inlet 3 and after passing through the filter means 5 leaves through the outlet 4.

Below the chamber 6 and communicating therewith there is positioned a chamber 7 separated from the former by a perforated base 50, which also acts as a support element for the filter means 5.

The chamber 7 serves to collect the water which separates from the fuel and is therefore filled with fuel in its upper part, the separated water
5 accumulating in the lower part.

On the base of the chamber 7 there is positioned a water level sensor 8 comprising a float 9, the specific gravity of which lies between the specific gravity of water and that of the fuel, and which is positioned in the
10 collection chamber 7 under the influence of the level of the water A which collects on the bottom. The float 9 is slidable along a vertical guide stem 12, which projects into the chamber 7 by passing through a lower port 70 located at the lowest point of the chamber and closed by the stem 12 in collaboration with a seal gasket 122.

15 In the interior of the stem 12 there is positioned a magnetic field sensor element 13, for example of reed or Hall type, which is activated when the float, in moving upwards as the level of the accumulated water increases, reaches a position in correspondence with the element 13.

The sensor element 13 is electrically connected to an electronic card 14
20 by two connection cables 130 and 131. Said card is connected to the engine control unit. When, by the effect of the water collected in the chamber 6, the float 10 reaches the level of the sensor 13, an electrical signal is generated and by way of the two conductor cables 130 and 131 is sensed by the electronic card 14, which makes it available to the engine
25 electronic control unit, to warn the user by a warning lamp positioned on the vehicle dashboard or by a different warning signal.

When the water maximum level signal is generated, the control card 14 activates withdrawal means for the water collected in the chamber 7. Said water withdrawal means are associated with the lower end of the filter 1, but are not illustrated or described in detail as they are of known type.

5 In the interior of the stem 12, in proximity to its free end, there is also present a temperature sensor 15 embedded in a layer of conductive resin 150, to measure the temperature of the fuel present in the chamber 7, this being equal to or at least indicative of the temperature of the fuel passing through the filter 1.

10 The sensor 15, for example of NTC type, is connected to the electronic card by two conductors 16 and 17. The temperature value measured by the sensor 15 is fed to the engine electronic control unit via the card 14. Figure 3 shows a variant of the invention in which one of the conductor cables connecting the sensor to the card 14 is also used as the conductor
15 cable connecting the sensor 15 to the card itself. Hence in this case there is simplification of the electrical circuit connecting the sensors to the card as the cable 20 is used as a common conductor.

Rec'd FCT/PTO 13 APR 2005

CLAIMS

1. A fuel filter for diesel engines with high pressure direct injection of common rail type and the like, comprising an outer casing provided with a fuel inlet conduit (3) and an outlet conduit (4), and internally housing a filter means, characterised in that a temperature sensor (15) is positioned in the lower part of said casing to measure the temperature of the fuel present in the casing.
2. A filter as claimed in claim 1, characterised in that said casing presents an upper chamber (6) for containing said filter means, and a lower chamber (7) communicating with said upper chamber to collect the water which said filter means (5) separates from the fuel, means (8) for measuring the level of the water collected in the chamber (7) being associated with said lower chamber.
- 3 A filter as claimed in claim 2 characterised in that said temperature sensor is associated with said means for measuring the water in the chamber (7).
- 4 A filter as claimed in claim 2 characterised in that said water level measurement means comprise a sensor positioned in the collection chamber to generate an electrical signal when the water level reaches a predetermined maximum value, said signal being fed to an electronic card.
- 5 A filter as claimed in claim 4 characterised in that said sensor means comprises a float positioned in the collection chamber and having a specific gravity between the specific gravity of water and that of the fuel, and a float guide stem in the interior of which there is positioned a

magnetic field sensor connected electrically to said electronic card by two conductors.

6 A filter as claimed in claim 5 characterised in that said temperature sensor is positioned in the interior of said stem in proximity to its free end,
5 and is connected electrically to said card by two conductors.

7 A filter as claimed in claim 6 characterised in that one of the conductors connecting said temperature sensor to said card is also connected to said magnetic field sensor.

8 A filter as claimed in claim 1, characterised in that said temperature
10 sensor is of NTC type.

9 A filter as claimed in claim 1, characterised in that said temperature sensor is embedded in a layer of conductive resin.

Box No. VIII (iii) DECLARATION: ENTITLEMENT TO CLAIM PRIORITY

The declaration must conform to the standardized wording provided for in Section 213; see Notes to Boxes Nos. VIII, VIII (i) to (v) (in general) and the specific Notes to Box No. VIII (iii). If this Box is not used, this sheet should not be included in the request.

Declaration as to the applicant's entitlement, as at the international filing date, to claim the priority of the earlier application specified below, where the applicant is not the applicant who filed the earlier application or where the applicant's name has changed since the filing of the earlier application (Rules 4.17(iii) and 51 bis.1(a)(iii)):

in relation to this international application, UFI FILTERS S.P.A. is entitled to claim priority of earlier application No. RE2002A000094, IT, 3 December 2002, by virtue of the following:

the applicant's name changed from UFI UNIVERSAL FILTER INTERNATIONAL S.P.A. to UFI FILTERS S.P.A. on January 01, 2003.

This declaration is made for the purposes of all designations.

☐ This declaration is continued on the following sheet, "Continuation of Box No. VIII (iii)".